

UP Series SP83 SOLAR POWER AGM



Product Design Features

- AGM-technology, maintenance free product (SMF).
- Power Supply & Starting power suitable.
- More than 500 cycles at 75% D.O.D.
- More than 1000 cycles IEC 61427.
- High resistance to deep and repetitive discharge cycles.
- Internal gas recombination efficiency 98%-99%.
- One-way valve regulated system with flame-arrestor.
- Delivered ready for use at 100% of its nominal capacity.
- Long Service Life.

Specifications

Nominal Voltage (V)		12
Capacity (Ah)	C1 (9.60V)	60
	C5 (10.20V)	70
	C10 (10.80V)	80
	C100 (10.80V)	85
	Cr (10.5V)	175 min
Dimension	Length (mm)	308
	Width (mm)	175
	Height (mm)	210
Weight (kg)		26.7
Box type		MB
Terminals		Standard cone
Handles		Yes (2)
QTY / PLT / Layer		42 / 1 / 3

Certification



- ISO 9001
- ISO 14001


Charging Type

Parameter / Limits


Charge with Constant Current	Current limit: 10 - 20% from C10 capacity rate
Charge with Constant Voltage	Voltage limit: 14.1 - 15.0V per block
Float Charge Voltage (Cycling)	Float voltage: 13.62V per block @ 20°C
Temperature Correction Factor	0.018V per block / °C



Battery Layout



25A and 20 hour Discharge Characteristics



Capacity vs Operating Temperature

